

HDC-2100M1080

Home | Security | HDcctv / HD-SDI | Boxed

HDC-2100M1080
1/2.8" HD-SDI Camera, Day&Night, 1920x1080, WDR,
3D-DNR, CS, 12VDC/24VAC

Art-Nr. 200838



Main Features

1/2.8" 2.0 Megapixel progressive scan CMOS-Sensor	3D-DNR powerful noise reduction
Resolution max. 1920 x 1080 (Full HD 1080p)	Integrated motion detection
1.5G HD-SDI video transmission via coax	DIS Digital image stabilization
Removable infrared cut filter (ICR)	Privacy zone masking
WDR (Wide Dynamic Range)	

Specifications

Series	eneo HD-SDI
System	day&night
Sensor size	1/2,8"
Imager	CMOS
Resolution	1920x1080 (16:9)
Frame rate	1080 @ 25/30p
Signal-to-noise ratio	-50 db
Sensitivity (at 50% video signal)	0,3 Lux, (colour)
Low speed shutter	yes, 2x ~64x
Digital Noise Reduction (DNR)	yes, 3D
Backlight compensation	BLC, HS BLC (eclipser), adjustable zones, ON/OFF switchable
Wide Dynamic Range (WDR)	yes, 68dB
White balance	ATW, automatic, AWC (Hold), manual
IR cut filter	switchable

HDC-2100M1080

(Continuation Specifications)

Day/Night switching	auto, By external contact closure, day, night
Privacy zones masking	ON/OFF switchable
OSD function control	privacy zones, digital noise reduction (DNR), shutter control, white balance, DIS, colour/B&W, BLC, language, text
Menu languages	English, German, French, Italian, Spanish, Russian
Text display	20 character labels
Activity detection	yes
Motion detector	4 zones, ON/OFF switchable
Mirror function	V flip, rotation, flip
Digital zoom	10x
e-PTZ support	yes
Lens mount	CS/C mount
Illumination	no
Video outputs	HD-SDI, 1x composite (CVBS)
External connections	alarm output, RS-485, voltage input
Serial interfaces	RS-485
Serial interfaces protocols	Fastrax, Pelco P, Pelco D
Alarm inputs	yes
Alarm outputs	16x TTL, open collector (terminal block)
Supply voltage	12VDC, 24VAC, (+/-10%)
Power consumption	3.6W
Housing	boxed
Colour	Pantone 877C, Side wings: Pantone Cool Gray 11C
Vandalism resistant	no
Protection rating	n/a
Temperature range (operation)	-10°C ~+50°C
Dimensions (HxWxD)	56x67,5x124
Weight	290g
Parts supplied	manual, C/CS adapter
Certificates	CE

Optional accessories

70536	VT-PS12DC-9	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. open Ends
70771	WD-23	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone 877
79644	VTL-WWD	Weatherproof Housing (300mm) RAL9002, Wallbracket, Thermostat, Heater 12-24V
43277	F02Z2.8DC-NFSHD	F1.2/2,8-8mm Lens, Varifocal, No Focus Shift, Full HD 1080p, 1/3" CS Mount

GENITECH Comptabilité

36 Rte de Montpellier · 34230 Vendémian · FR
Phone - 01.49.63.74.41 · Telefax - 01.49.63.74.51
genitech@genitech.fr · — www.genitech.fr

