

PXD-1210Z03

Home | Security | IP Domes | Megapixel Fixed

PXD-1210Z03
1/2.7" Network Dome, Fixed, Day&Night, 1920x1080,
PoE, 3x Auto Focus Zoom, ONVIF

Art-Nr. 207189



Main Features

1/2,7" Progressive scan CMOS-Sensor
Full HD 1920x1080 Pixel, Real-time
Simultaneous video streaming (H.264 & MJPEG)
Optical 3x auto focus zoom, 3-9mm
Removeable infrared cut filter (ICR)
Motion detection, privacy masks

Plastic indoor dome housing
D-WDR and 3-DNR noise reduction
Audio and alarm in-/outputs
Quick and reliable installation
PoE, microSD card support
ONVIF support

Specifications

Series	eneo PXD
Resolution standard	HD 1080p
System	True Day&Night
Sensor size	1/2.7"
Imager	CMOS, Omnivision Progressive Scan CMOS
Sensitivity	0,2 Lux, (colour) 0,02 (B&W)
Automatic electronic shutter (ESC)	1/1,5~1/10.000sec.
Digital Noise Reduction (DNR)	yes, 3D- DNR
Low speed shutter	yes, 1/1.5~1/425sec.
White balance	automatic, ATW, manual
Backlight compensation	BLC
Wide Dynamic Range (WDR)	D-WDR
IR cut filter	switchable

PXD-1210Z03

(Continuation Specifications)

Mirror function	180° rotation, flip
Resolution max.	1920x1080
Resolution	1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 1024x768 (4:3), 800x600 (4:3), 720x576 (4:3), 640x480 (4:3), 352x288 (4:3)
Image transmission rate max.	25 fps
Privacy zones masking	ON/OFF switchable
Activity detection	yes
Motion detector	4 zones, ON/OFF switchable
Analysis functions	motion analysis, obstruction detection
Menu languages	German, English, French, Spanish, Italian, Russian, Portuguese
OSD function control	resolution, motion detection, WDR, bit rate, digital noise reduction (DNR), shutter mode
External connections	voltage input, RJ-45, alarm input, alarm output, audio in/output
Video outputs	CVBS
Audio support	yes
Audio	1/1 Line input and output
Audio standards	G.711, G.726
Alarm inputs	1
Alarm outputs	1
Alarm processing	SD-card recording, FTP, E-Mail
Internal storage	microSD card, SD-HC 32GB
	H.264, M-JPEG
Stream types	3 streams H.264, 1 stream MJPEG multiple
Ethernet interface	10Base-T, 100Base-TX
Web browser	MS Internet Explorer vers. 7.0 or higher, Safari (Java), Mozilla Firefox (Java, Quick time), Google Chrome (Java)
Network protocols	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PP-PoE, UPnP, IGMP, SNMP, IPv4, IPv6
Multicast compliant	yes
Lens type	auto focus zoom
Zoom factor	3x
Focal length	3 mm - 9 mm
Horizontal angle of view	108° - 41°
Aperture range	F1,32~F2,1
Digital zoom	8x
Iris control	DC
Illumination	no
Remote configuration	web browser, remote software
Password protection	administrator & users, yes
e-PTZ support	no

PXD-1210Z03

(Continuation Specifications)

Rotation range	+/-177,5°
Vertical tilt range	27° ~+90°
Supply voltage	12VDC, 24VAC, PoE
Power over Ethernet	IEEE 802.3af
Blower	no
Heater	no
Power consumption	8W
Mounting	wall mount, ceiling mount
Temperature range (operation)	n/a
Vandalism resistant	no
Housing	indoor
Housing material	plastic, metal
Colour (housing)	RAL9003
Colour (bubble)	clear
Protection rating	n/a
Management Software Support	www.eneo-security.com/software
SDK	upon request
ONVIF	ONVIF Test Tool Version 12.06 (Profile S)
Certificates	CE, FCC
Dimensions (HxWxD)	99,53x149mm
Weight	520 g
Parts supplied	manual, Torx key, screw set

Optional accessories

204193	PNR-5104	Network Video Recorder, 4xIP, 1920x1080, 120fps, 1TB, H.264, MPEG-4, M-JPEG
204192	PNR-5108	Network Video Recorder, 8xIP, 1920x1080, 200fps, 1TB, H.264, MPEG-4, M-JPEG
202563	PNR-5116	Network Video Recorder, 16xIP, 1920x1080, 320fps, 1TB, H.264, MPEG-4, M-JPEG
202562	PNR-5216	Network Video Recorder, 16xIP, 1920x1080, 480fps, 1TB, H.264, MPEG-4, M-JPEG, DVI, D-Sub

GENITECH Comptabilité

36 Rte de Montpellier · 34230 Vendémian · FR
Phone - 0811.040.048· Telefax - 01.49.63.74.51
genitech@genitech.fr · — www.genitech.fr

