




VM-HD19M

SKU: 229199



19" (48cm) LCD, Professional Monitor, 1280x1024, 12V, Protection Glass , HDMI, VGA

Main Features

Professional 19" (48 cm) LCD monitor	Fast response time 5ms
Built to run 24x7x365 continuously (Industrial Level)	Different video inputs HDMI, VGA, BNC (CVBS)
Including protection glass, Anti-Glare-Display 3H	Audio In- and Output
Extended temperature range -30°C ~+85°C	Built-in speakers
Maximum resolution 1280x1024 pixels	Supply voltage: 12VDC
LED Back Light	Metal cabinet including stand

Specifications

Applications	24/7, Industrie
Resolution Pixels	1280x1024
Housing color	black
Housing material	metal
Backlighting	LED
Screen size (inch)	19"
Screen size (cm)	48 cm
Aspect ratio	5:4
Viewing angle vertical	178°
Viewing angle horizontal	178°

VM-HD19M

Continuation of the specifications

Brightness typical	350 cd/m ²
Contrast ratio typical	1000:1
Reponse time typical	5 ms
Video inputs (type)	composite (CVBS), HDMI, VGA
Loudspeaker	2
Video outputs 2	Composite (CVBS)
Audio inputs	1
Serial interfaces	no
Power consumption	20W
Operating temperature	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Manufacturer order number	229199

Optional Accessory

SKU	Name	Description
224229	VM-LCDWMB2	Wall bracket for LCD monitors horizontal adjustable, support up to max. 8 kg
228560	VM-TSHA	Monitor stand high adjustable up to 130mm, for LCD-Monitors, 15-27 Inch, maximum 10Kg

Your contact person

SARL GENITECH
 108 Rue Henri Barbusse
 95100 Argenteuil
 FR
 Tel: 0139472651
 E-Mail: genitech@genitech.fr
 Web: www.genitech.fr

