



VM-SD8M

Article number: 229215

8" (20,3cm) LCD Monitor SD, 1024x768, LED, HDMI, VGA, Composite

Specifications

Display:	
Resolution	1024x768 (4:3)
Aspect ratio	4:3
Resolution pixels	1024x768
Display element	Colour TFT/LCD
Contrast ratio typical	700:1
Response time typical	5 ms
Brightness typical	250 cd/m ²
Backlighting	LED
Viewing angle vertical	150 °
Viewing angle horizontal	160 °
Screen size	8
Screen Size (cm)	20,3 cm
Pixel format	0,158mm x 0,158m
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC

Features:	
Comb filter	3D Motion Adaptive De-interlace
Menu languages	English

Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, composite (CVBS)
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3,5mm jack
Serial interfaces	no

General:	
Dimensions (HxWxD)	148,8x189,9x43mm
Mount	VESA standard 75x75mm
Housing material	metal
Housing color	black
Weight	2.5 kg
Loudspeaker	2
Power consumption	10W
Supply voltage	12VDC
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)

Scope of delivery:	
Parts supplied	manual, power cord, PSU 100-240VAC, feet, IR remote controller, HDMI cable

Related Products



VMC-LCD/WCMB-1 | SKU: 90394



LCD-ST/CM1 | SKU: 90491



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

