

# DLR4-16/2.5TBDV

Home | Security | Recording | DVR

DLR4-16/2.5TBDV  
Digital Video Recorder (16 Channels), H.264,  
2.5TB, 400fps, 704x576, DVD-RW

Art-Nr. 73193



## Main Features

<b>Pentaplex operation</b>	<b>Secondary storage / Archiving via USB 2.0 &amp; DVD RW</b>
<b>H.264 video compression standard</b>	<b>2500Gbyte SATA HDD (no HDD extension possible)</b>
<b>Recording speed: 400 ips max.</b>	<b>Live picture &amp; playback zoom (4x)</b>
<b>Video resolution: 704x576 px. max.</b>	<b>Browser access &amp; RASPlus/RAS mobile remote control</b>
<b>16 loop-through inputs / VGA, composite outputs</b>	<b>IR remote control and mouse control</b>
<b>Network connectivity (10/100Base-T Ethernet)</b>	<b>PTZ control through RS-485 port</b>

## Specifications

<b>Series</b>	eneo DLR
<b>Operation mode</b>	Pentaplex
<b>Video standard</b>	PAL/NTSC (automatic selection)
<b>Video inputs (amount)</b>	16
<b>Video inputs</b>	1Vp-p, (C)VBS, 75ohms, BNC (loop-through)
<b>IP channels</b>	-
<b>Main video outputs</b>	VGA, composite (CVBS)
<b>Video outputs</b>	1Vp-p, 75ohms, BNC
<b>Spot monitor</b>	composite (CVBS)
<b>Audio inputs</b>	-
<b>Alarm inputs</b>	16x TTL, programmable as NC/NO
<b>Motion detector</b>	programmable 32 x 24 (768) masking grid, 5 sensitivity levels, minimum field size: 256 levels, video signal obscuration and video signal blind detection

# DLR4-16/2.5TBDV

(Continuation Specifications)

<b>Covert camera mode</b>	available
<b>Alarm triggers</b>	system error, disk error, acoustic
<b>Alarm outputs</b>	2x NO/NC contact
<b>Alarm notification</b>	e-mail, remote software (RASplus), callback
<b>Alarm reset input</b>	TTL input
<b>Event logs</b>	no limit for alarm-in, motion, video loss, text-in
<b>Max. recording resolution</b>	704x576
<b>Compression standard</b>	H.264, (H.264: advanced compression engine provides smaller data size without significant picture quality distortion)
<b>Max. recording rate</b>	400 B./Sek., @ 352 x 288
<b>Digital storage media</b>	SATA hard disk
<b>Harddisk capacity (internal)</b>	2,5 TB
<b>Max. harddisk capacity (internal)</b>	6 TB
<b>Recording</b>	permanent, movement, timer, panic, event
<b>Digital signature</b>	watermark
<b>Pre-alarm recording</b>	up to 30min.
<b>Post-alarm recording</b>	up to 15min.
<b>Playback</b>	full screen, 4 channel split, 9 channel split, 16 channel split, PiP
<b>Playback speed</b>	400 ips. at CIF (352x288 Px.), 200 ips. at 2CIF (704x288 Px.), 100 ips. at 4CIF (704x576 Px.) / PAL
<b>Zoom function</b>	2x~4x
<b>Search function</b>	date/time, record table, calendar, event, motion, museum, text
<b>Integrated writer</b>	DVD
<b>Secondary Storage</b>	via USB 2.0. Network Data Export: Clip Player, AVI, JPG, BMP
<b>Control units (external)</b>	system keyboard, mouse
<b>Remote access</b>	remote software, Microsoft Internet Explorer
<b>Mobile access</b>	iPhone, PDA
<b>Menu languages</b>	Danish, German, English, French, Dutch, Italian, Polish, Spanish, Russian, Czech, Hungarian
<b>Network</b>	10/100 Base-Tx, RJ45
<b>Network protocols</b>	TCP/IP, DHCP, SMTP, PPPoE
<b>Transmission rate (Network)</b>	100 ips (CIF), 50 ips (2CIF), PAL
<b>Interfaces external storage</b>	USB, 2x USB 2.0
<b>Serial interfaces</b>	RS-485, RS-232, RS-485 for telemetry control (proved protocols: eneo-Fastrax, Pelco P&D) or remote keyboard control
<b>Text insertion interface</b>	ATM/POS, 10 chann. max.
<b>Password protection</b>	64 groups, 256 users
<b>Supply voltage</b>	100VAC ~240VAC, 0.6A 50/60Hz
<b>Power consumption</b>	40W
<b>Temperature range (operation)</b>	+5°C ~+40°C

# DLR4-16/2.5TBDV

(Continuation Specifications)

<b>Housing</b>	steel metal with plastic front, desktop design
<b>Colour</b>	Pantone 427C
<b>Dimensions (HxWxD)</b>	88x430x405mm
<b>Weight</b>	7.4kg
<b>Parts supplied</b>	IR remote controller, 19" rack mount angle, power cord, Viewer CD ROM (RASplus), manuals
<b>Certificates</b>	CE

## Optional accessories

<b>74149</b>	<b>KBD-2</b>	System Keyboard with 3-Axis Joystick and Jog Shuttle, 12VDC
<b>74746</b>	<b>KBD-NSC-100</b>	Network System Controller with 3-Axis Joystick and Jog Shuttle, 5VDC
<b>71902</b>	<b>USB-MOUSE</b>	USB Mouse for Recorder Series DMR, DPR, BLR and DLR3/4 - PS/2, USB
<b>72998</b>	<b>HDD-2000SATA</b>	Hard Disk Drive 2TB, SATA for eneo BLR, DLR, DMR Series

# DLR4-16/2.5TBDV

## Product information

The eneo DLR4 series Pentaplex recorders feature a very efficient compression method (H.264) and a high record and playback speed. As a result they only take up approximately 8K (NTSC) for one best quality image, which is significantly less than comparable models. Recorder series is network compatible and are equipped with supporting remote software. This software enables access to live pictures and recorded images in single or multi-image mode without interrupting recording. Graphical 11 language user interface, telemetry function, USB 2.0 interface to be used for the purpose of expanding internal storage capacity and for quick and easy archiving on external hard disk or CD-RW.

GENITECH

108, rue Henri Barbusse - 95100 Argenteuil - FR  
Phone - 01.49.63.74.41 - Telefax - 01.49.63.74.51  
ecorbeau@genitech.fr - [www.genitech.fr](http://www.genitech.fr)

