

analog Fixed Dome Cameras



Model	WV-CW364	WV-CW334	WV-CF504	WV-CF324	WV-CF294/284	WV-CF354/344
Camera Type	Outdoor Vandal	Outdoor Vandal	Indoor Minidome	Ruggedized Indoor Minidome	Indoor Minidome	Indoor Minidome
Wide Dynamic	No	No	SD5	No	No	No
Imaging Device	1/3"	1/3"	1/3"	1/4"	1/4"	1/3"
Day/Night	Yes	Yes	Yes	Yes	Yes	Yes (Electrical)
Removable IR (D & N)	Yes	No	Yes	No	No	No
Focus	N/A	N/A	Auto Back Focus	Auto Focus	WV-CF294: Auto Focus WV-CF284: N/A	WV-CF354: Auto focus WV-CF344: N/A
Minimum Illumination <small>(w/clear dome when applicable)</small>						
Color	0.6lux	0.6lux	0.1lux	0.9lux	0.9lux	0.08lux
Color w/enhancement	N/A	N/A	0.003lux (32x sens up)	N/A	N/A	0.0025lux (32x sens up) 0.00016lux (512x sens up)
B/W	0.05lux	0.4lux	0.01lux	0.6lux	0.6lux	0.05lux
B/W w/enhancement	N/A	N/A	0.0003lux (32x sens up)	N/A	N/A	0.0016lux (32x sens up) 0.00010lux (512x sens up)
Key Features	Adaptive Black Stretch	Adaptive Black Stretch	Intelligent VMD (object abandonment/ removal, loitering, direction)	Adaptive Black Stretch	Adaptive Black Stretch	Adaptive Black Stretch Lens Distortion Compensation
Horiz. Resolution	540 lines	540 lines	650 lines	540 lines	540 lines	650 lines
Focal Length	2.8-10.0mm vari-focal	2.8-10.0mm vari-focal	3.8mm-8.0mm vari-focal CS lens mount	2.8mm-10.0mm vari-focal	WV-CF294: 2.8-10.0mm vari-focal WV-CF284: 2.8-6.0mm vari-focal	2.8-10mm vari-focal
Zoom	3.6x optical	3.6x optical	2.1x optical/ 2x digital	3.6x optical	WV-CF294: 3.6x optical WV-CF284: 2.1x optical	3.6x optical/ 2x digital
Motion Detection	No	No	i-VMD (Intelligent VMD)	No	No	Yes
On Screen Display	No	No	Yes	No	No	Yes
Image Stabilization	No	No	Yes	No	No	Yes
Light Control	ALC	ALC	ALC/ALC+	ALC	ALC	ALC/ALC+/ELC
IP66	Yes	Yes	No	No	No	No
Power	24VAC/12VDC	24VAC/12VDC	24VAC/12VDC	24VAC/12VDC	24VAC/12VDC	24VAC/12VDC
Power Consumption	AC 2.9 W (w/o heater) AC 13.1 W w/heater DC 250mA (w/o heater)	AC 2.9 W (w/o heater) AC 13.1 W w/heater DC 250mA (w/o heater)	AC 3.4 W DC 280mA	AC 2.7 W DC 220mA	WV-CF294: AC 3.0 W DC 265mA WV-CF284: AC 2.7 W DC 220mA	AC 2.1 W DC 180mA
Operating Temp.	14°F – 122°F -22°F – 122°F When optional heater used	14°F – 122°F -22°F – 122°F When optional heater used	14°F – 122°F	14°F – 122°F	14°F – 122°F	14°F – 122°F