

# 1/2" High Sensitivity Camera

## HDC-S308M1080



2MP 30x AF HD-SDI Box Camera



### Features

- 1/2" 2MP Sony CMOS sensor
- HD-SDI, EX-SDI, TVI, CVBS
- 30x Optical Zoom(6 ~ 180mm) & 32x Digital Zoom
- Real-time True WDR
- Digital Noise Reduction(2D+3D)
- Digital Slow Shutter
- Digital Image Stabilization
- Privacy Mask Function
- High Light Compensation
- Defog Function
- ACE(Digital WDR)
- Motion Detection
- Protocol(VISCA, Pelco-D, Pelco-P)

MODEL		HDC-S308M1080		
<b>CAMERA</b>				
Image Sensor	1/2" Sony CMOS Sensor			
Total Pixels	1952(H) x 1241(V) = 2.42M Pixels			
Active Pixels	1937(H) x 1097 (V) = 2.12M Pixels			
Video Format	1080p@60/50fps, 1080p@30/25fps, 720p@60/50fps, 720p@30/25fps			
Min. Illumination	Color	0.15 lux / DSS 0.0375 lux		
	BW	0.01lux / DSS 0.002 lux		
S/N Ratio	more than 50dB (AGC off)			
Video Output	HD-SDI, EX-SDI, TVI, CVBS			
<b>LENS</b>		<b>30x</b>		
Lens Type	30x Day & Night Zoom Lens			
Zoom Ratio	Optical 30x, Digital 32x Zoom			
Focal Length	f = 6.0 mm ~ 180.0 mm			
Aperture Ratio	F1.5 (wide) ~ F4.3 (tele)			
Angle Of View (D, H, V)	WIDE	68.6°	61.2°	35.7°
	TELE	2.65°	2.32°	1.31°

<b>CAMERA FUNCTIONS</b>	
Camera Title	ID / Title / Zoom Ratio / System Message
Day & Night	Auto / Day / Night / Ext-in
WDR/BLC	Off / WDR / BLC / HLC
ACE	Off / Low / Middle / High
DNR	Auto / Off / Low / Middle / High
Defog	Off / On(Auto / Manual)
Image Stabilization	Off / On
Motion Detection	Off / On (3 positions)
Privacy Mask	Off / On (24 positions)
Digital Slow Shutter	Off /x2 /x4
Gain Control	Off / On
White Balance	Auto / One Push / Manual / Indoor / Outdoor
Shutter Speed	1/30(25) ~ 1/30,000 sec
E.Zoom	Off / x2 ~ x32
Digital Flip	Off / H / V / H&V

<b>GENERAL</b>	
Power Source	DC12V±10%
Power Consumption	Max 500mA
Operating Temperature	-10°C ~ +50°C / 0% ~ 90% RH
Dimensions	72.8(W) x 80(H) x 162.5(D) mm
Weight	0.82Kg

### Dimensions

Unit : mm

