



Thermal IP Bullet Camera

NVIP-H-8041/T



FUNCTIONS



KEY FEATURES

- Lens: thermal, f=50 mm/F1.0
- Video content analysis
- SD card support
- Temperature Measurement
- Temperature Alarm
- Ability to observe in total darkness

DIMENSIONS



| | |
|------------------------------------|---|
| Image - Thermal Module | |
| Image Sensor | Uncooled FPA Microbolometer |
| Number of Effective Pixels | 400 (H) x 300 (V) |
| Pixel Size | 17 µm |
| Spectral Range | 8 - 14 µm |
| Thermal Sensitivity | 40 mK |
| Thermovision Modes | White Hot, Black Hot, Rainbow, Ironbow, HSV, Autumn, Bone, Cool, Copper, Fire Hot, Pink, Spring, Summer, Winter, Jet, Flame, Rosebengal |
| Detection Temperature | -40°C ~ 150°C |
| Lens - Thermal Module | |
| Lens Type | f=50 mm/F1.0 |
| Object Detection Range | 1471m - human , 4510m - vehicle |
| Object Recognition Range | 368m - human , 1127m - vehicle |
| Image | |
| Digital Noise Reduction (DNR) | 2D, 3D |
| Defog Function (F-DNR) | yes |
| Network | |
| Stream Resolution | 704 x 576, 704 x 480, 352 x 288 (CIF), 352 x 240 |
| Frame Rate | 25 fps for 704 x 576, 30 fps for 704 x 480 and lower resolutions |
| Multistreaming Mode | 2 streams |
| Video/Audio Compression | H.264, H.264 Smart, H.265, H.265 Smart, MJPEG/G.711, RAW_PCM |
| Number of Simultaneous Connections | max. 8 |
| Bandwidth | 15 Mb/s in total |
| Network Protocols Support | HTTP, TCP/IP, IPv4/IPv6, UDP, HTTPS, FTP, DHCP, DNS, RTSP, RTP, PPPoE, SMTP, RTCP, Unicast |
| ONVIF Protocol Support | Profile S |
| Camera Configuration | from Internet Explorer browser languages: Polish, English, Russian, and others |
| Compatible Software | NMS |
| Other functions | |
| Temperature Measurement | yes |
| Temperature Alarm | yes |
| Temperature Measurement Zones | 19 polygon, line, point |
| Privacy Zones | 5 |
| Motion Detection | yes |
| Video Content Analysis (VCA) | tamper, abandoned object, object disappearance, line cross, zone entrance, double line cross, loiter, multi loiter, abnormal speed, converse, illegal parking |
| Image Processing | 180° image rotation, mirror effect |
| Prealarm/Postalarm | up to 5 MB/up to 86400 s |
| System Reaction to Alarm Events | e-mail, saving file on FTP server, saving file on SD card, alarm output activation |
| Interfaces | |
| Video Output | BNC, 1.0 Vp-p, 75 Ohm - maintenance only |
| Audio Input/Output | 1 x RCA/1 x RCA |
| Alarm Input/Output | 2 (NO/NC)/2 |
| RS-485 | yes |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Memory Card Slot | SD - capacity up to 128GB |
| Installation parameters | |
| Dimensions (mm) | with bracket: 110 (Ø) x 388 (L) |
| Weight | 1.9 kg |
| Degree of Protection | IP 66 (details in the user's manual) |
| Enclosure | aluminium, white, fully cable managed wall mount bracket in-set included |
| Power Supply | PoE, 12 VDC |
| Surge protection | TVS 4000 V |
| Power Consumption | 6 W |
| Operating Temperature | -40°C ~ 60°C |
| Humidity | max. 90% relative (non-condensing) |

Motion Detection function and seven Temperature Measurement Zones available from firmware version v2.0.0603.1002.89.0.160.0.11.