




# MULTI-FUNCTIONAL RELAY

The relays copy the selected PG outputs of the control panel, in the multifunctional version they can also react to the activation of unidirectional detectors in the JA-15x range.



Product code	AC-160-DIN	AC-160-C
Product name	Wireless multifunctional relay for DIN-rail installation	Wireless multifunctional relay
Product type	wireless 	wireless 
Dimensions	18 x 90 x 65 mm	49 x 49 x 26 mm
Power supply	230 V / 50 Hz	100 - 230 V / 50 - 60 Hz
Operating frequency	868.1 MHz	868.1 MHz
Internal power consumption	0.5 W / max. 1.7 W	0.2 W / max. 0.7 W
Max. switched voltage	250 V AC	250 V AC
Maximum switched current	16 A	16 A
Inductive, capacitive load	8 A	8 A
Minimum switched DC power	0.5 W	0.5 W
Halogen lighting	max. 1000 W	max. 1000 W
Diameter of connected conductors	max. 2 x 1.5 mm <sup>2</sup> max. 1 x 2.5 mm <sup>2</sup>	max. 2 x 1.5 mm <sup>2</sup> max. 1 x 2.5 mm <sup>2</sup>
Operating temperature	-10 °C to +40 °C	-10 °C to +40 °C



## UR-01

Universal relay

-

18 x 90 x 65 mm

230 V / 50 Hz

-

0.3 W / max. 0.8 W

250 V AC / 24 V DC

16 A

8 A

0.5 W

max. 1000 W

max. 2 x 1.5 mm<sup>2</sup>  
max. 1 x 2.5 mm<sup>2</sup>

-10 °C to +40 °C

