



SOL-IQbox-plus Article number: 215020

Camera junction box for video surveillance with outlet, lightning protection 400x300x150mm

Optimised for outdoor use Electrically prewired for flexible, modular expansion. UV stable polycarbonate, corrosion-resistant Protective class IP66 Impact resistance IK 10, vandalism protected Swivelling door (with door contact switch) Wall or mast mounted Fast, easy installation Simple mechanical finishing

Junction box for universal expansion with a variety of components from different manufacturers and in different designs. The additional components may be mounted either on mounting plates using hook and loop strap without requiring tools, or using a TS35 mounting rail, which is also included in the scope of delivery.

Specifications

Housing:	UV resistant polycarbonate, RAL 7035, seal: PUR		
Door:	Swivelling, opening angle 120°		
Closure:	2-point closure, 2 locks lockable		
Exterior dimensions:	400 x 300 x 150mm		
Protective class:	IP66, IK10		
Temperature range:	-20°C to +55°C		
Cable glands:	1 x M16x1.5		
	3 x M20x1.5		
	1 x M25x1.5		
	1 x M25x1.5 – separable (suitable for network wiring)		
	All cable entries ex works incl. sealing plugs		
Voltage input:	230V/50Hz		
1. Mounting rail TS35:	With terminals, mounted, 20mm elevated for placing cables underneath		
2. Mounting rail TS35:	With included fastening materials		
Service outlet	Protective contact outlet		
Personnel protection:	FI Circuit breaker Siemens 5SU1354-6KK16		
Lightning protection:	Lightning protection combination arrestor type 1+2+3 Citel DS132VGS- 230/G		
Other:	Door alarm contact, mounted and wired to terminals,		
	3x hook and loop strap,		
	2x pressure compensation element mounted		

Optional accessories

209744	SOL-WST-MB-30	Mast attachment 30cm
209743	SOL-WST-WB	Wall mounting

www.videor.com



Your contact person



Solvido is a registered trademark of VIDEOR E. Hartig GmbH Carl-Zeiss-Straße 8 63322 Rödermark Germany Phone: +49 6074-888-111 E-mail: info@videor.com Internet: www.videor.com