



VKC-13002

Article-No.: 204492

1/3" Cylindric Camera, Colour,
3.6mm, 700TVL, 12VDC

Mainfeatures

Cylindric colour CCD Camera
OSD menu via inner joystick
Backlight compensation (BLC)
Sensitivity of 0.1Lux
Mounting stand with swivel head

1/3" 960H Sony EXview HAD CCD II
Wide-Dynamic-Range function D-WDR
Motion detection, privacy zones
Weatherproof aluminium housing (IP67)
Compact version (23mm outside diameter)

Specifications

System	electronic Day&Night
Sensor size	1/3"
Imager	CCD
Imager	960H Sony EXview HAD CCD II
Active picture elements	976(H) x 582(V) pixels
Synchronization	internal
Signal-to-noise ratio	50dB
Gamma correction	0.45
Horizontal resolution	700 TVL
Sensitivity	0,1 Lux
Automatic electronic shutter (ESC)	1/50 - 1/100.000sec.
Manual electronic shutter (MES)	1/50 - 1/10.000sec.
Low speed shutter	no
Automatic gain control (AGC)	yes
Digital Noise Reduction (DNR)	2DNR
White balance	ATW, push, user defined, Anti CR, manual, push lock
Backlight compensation	BLC, HLC

Specifications (continued)

Wide Dynamic Range (WDR)	D-WDR
Aperture Correction (APC)	horizontal and vertical
IR cut filter	OLPF (Overlay Low Pass Filter)
Video outputs	composite (CVBS)
Lens type	fixed focal length
Focal length	3,6 mm
e-PTZ support	no
Digital zoom	no
Horizontal angle of view	69°
Illumination	no
Menu languages	English, German, French, Russian, Portugese, Spanish, Japanese, Chinese
Activity detection	yes
Privacy zones masking	4 areas, masking, X/Y start/end
Serial interfaces	no
External connections	Video (BNC), 12 VDC (DC socket)
Temperature range (operation)	-10°C ~ +50°C
Housing material	aluminium
Integrated wall mount	no
Hidden cable management	no
Sunshield	no
Window heater	no
Colour (housing)	black
Vandalism resistant	no
Protection rating	IP67
Alarm inputs	-
Alarm outputs	-
Supply voltage	12VDC
Power consumption	1W
Weight	72g
Parts supplied	Camera, Wall bracket, Manual
Certificates	CE

Your partner for eneo products:

