



VK-134

Article-No.: 91747

1/3" Board Camera, B&W, 3.6mm,
420TVL, Housing, 12VDC

Mainfeatures

CCD b&w board camera with housing
Resolution of 380 horizontal lines
Internal synchronization
Interchangeable lens element

1/3" CCD Sensor
Automatic shutter control (ESC)
High sensitivity
Supply voltage: 12VDC



Specifications

System	black&white
Video standard	CCIR
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Active picture elements	290,000 (H) 500 x (V) 582
Synchronization	internal
Gamma correction	0.45
Horizontal resolution	420 TVL
Sensitivity	0,58 Lux
Sensitivity	at F1.2 (measured), 50 IRE
Automatic electronic shutter (ESC)	1/50 ~ 1/100,000sec.
Low speed shutter	no
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no
Aperture Correction (APC)	yes
IR cut filter	no

Specifications (continued)

Video outputs	composite (VBS)
Lens type	fixed focal length
Lens	F2.0/3.6mm
Focal length	3,6 mm
e-PTZ support	no
Digital zoom	no
Horizontal angle of view	69°
Iris control	no
MOD (Minimum object distance)	0,1 m
Illumination	no
Activity detection	no
Serial interfaces	no
External connections	Video (BNC), 12 VDC (DC socket)
Temperature range (operation)	-10°C ~ +50°C
Housing material	aluminium
Housing	indoor
Integrated wall mount	no
Hidden cable management	no
Sunshield	no
Window heater	no
Colour (housing)	black
Vandalism resistant	no
Protection rating	n/a
Alarm inputs	-
Alarm outputs	-
Supply voltage	12VDC
Supply voltage	12 VDC (+/-10%)
Power consumption	1.2W
Dimensions (HxWxD)	32x32x28mm
Weight	48g
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	H0225M	F2.5/2.5mm Board Camera Lens, 1/3" M12X0.5
	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug



Your partner for eneo products:

