



VM-FHD27MP

Article number: 217918

27" (69cm) LCD Monitor, FHD, 1920x1080, LED, HDMI, VGA CVBS, Protection Glass

Professional 27" (69 cm) LCD monitor	Perfect presentation through digital 3D filtering and noise reduction
Industrial design built to run 24x7x365 continuously	Different video inputs HDMI,VGA, Composite
Protective glass for harsh environmental conditions	Built-in speakers
Maximum resolution 1920x1080 pixels	Supply voltage: 240-100VAC, 50/60Hz
LED Back Light	Metal cabinet including stand
Fast response time 5ms	

Specifications

Display:	
Resolution	1920x1080 (16:9)
Synchronization	internal
Aspect ratio	16:9
Resolution pixels	1920x1080
Display element	Colour TFT/LCD, Anti-Glare-Display, Hard coating (3H), Haze :25%
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	350 cd/m²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	27"
Screen Size (cm)	68,6 cm
Pixel format	0,1617mm x 0,1617mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, composite (CVBS)
Audio inputs	1x 3.5mm jack, 2
General:	
Dimensions (HxWxD)	378x617x56mm
Mount	VESA standard 100x100mm, VESA standard 75x75mm
Housing material	metal
Housing color	black
Weight	6,7kg
Loudspeaker	2
Power consumption	40W
Supply voltage	100 ~ 240VAC, 50/60Hz
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, power cord, feet, IR remote controller, HDMI cable

Related Products



VM-LCDWB1 | SKU: 224228



VM-TSFA | SKU: 228500

www.eneo-security.com

More product information

Protection glass



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

